EXPLORER 510

Ultra-Portable Satellite Companion



September 2014 Product Sheet

The most important thing we build is trust



A rugged BGAN fit for purpose

The all new EXPLORER 510 is the smallest ever EXPLORER BGAN and the ideal combination of performance and portability.

The durable magnesium casing and a dust and water resistant design makes the EXPLORER 510 the perfect choice when working off the beaten track, but still dependant on a reliable connection



Specifications

Dimensions

Dilliciisions	
Total H / W / D:	202 / 202 / 51.8 mm
	7.8 / 7.8 / 1.6 inches
Weight (incl. battery):	1.4kg / 3.1lbs
Data capabilities	
Standard IP:	Up to 464 kbps
Streaming IP:	32, 64, 128 kbps
Voice capabilities	
Standard voice:	4 kbps
Premium voice:	3.1 kHz audio, 64 kbps
Text capabilities	
SMS:	160 characters
Inmarsat frequencies:	1518.0 - 1525.0 MHz (Rx) (EMEA)
	1525.0 - 1559.0 MHz (Rx)
	1626.5 - 1660.5 MHz (Tx)
	1668.0 - 1675.0 MHz (Tx) (EMEA)
EIRP:	15.1 dBW ±1dB

UK, FR, DE, ES, RU, JP and CN Languages:

User interface: Two LED (WLAN, Status), 1 Power Button USB Host Cobham web interface

CE, FCC, IC Approvals:

Inmarsat Class 2 Type Approval

Subject to change without further notice





Portable performance

Smaller than a standard laptop and weighing less than 1.4 kg, this satellite terminal is easy to carry along when travelling the world.

It supports your need for performance and provides simultaneous high quality voice and broadband access at speeds up to 464 kbps.

Connect the optional EXPLORER LTE Modem to the USB port and turn your device into a true communication SmartHub. Use local cellular net when available and BGAN if no other option.

Satellite connectivity made simple

EXPLORER 510 is easy to set-up and to operate. The user interface is intuitive and can be accessed from your PC or any kind of smart device

With the EXPLORER Connect App you can use your smart device to make calls or easily access the internet even in areas with no terrestrial or cellular coverage. The EXPLORER Connect App with a SIP softphone will be available on Android and IOS.

Interfaces

WLAN Access Point

IEEE 802.11 b/g/n

1 x USB host interface

2.0 (host) Version: Charging: Up to 1A

1 x BGAN SIM-Card slot

Environmental conditions

Temperature

Operational (ambient): -25°C to +55°C / -13°F to +131°F -40° C to $+80^{\circ}$ C / -40° F to $+176^{\circ}$ F Storage (excl. battery):

Battery storage temperature

1 month:	-20° C / -4° F to $+60^{\circ}$ C / $+140^{\circ}$ F
3 months:	-20°C / -4°F to +45°C / +113°F
1 year:	-20° C / -4° F to $+20^{\circ}$ C / $+68^{\circ}$ F
Relative humidity:	95% non-condensing
	at +40°C/+104°F
Robustness:	0.5 m/1.64 ft drop on concrete
	(operational, 95% survival)

-40°C to +80°C Storage temperature: -40°F to +176°F

Water and dust IP-66 Compiant (TBC)

Power

DC input range:	10.5-32VDC
Power consumption	
Standby / transmit:	0.8W / 14W (typical)
During charging:	38W (max.)
Connector type	2.5mm EIAJ RC-5320-IV

Input:	100-240VAC, 47-63Hz, 50W 19VDC	
Output:		
Built-in Battery:	Lithium ion (rechargeable)	
Stand-by time (TBC):	36h, 0°C/+32°F to 55°C/+131°	
Standard call:	3h, 0°C/+32°F to 55°C/+131°	
Premium voice call:	1h30m, 0°C/+32°F to +55°C/+131°F	
Receive time, max.:	3h30m @ 128kbps (25°C / 77°F)	
Transmit time, max.:	2h15m @ 128kbps (25°C / 77°F)	
Min. number of charges:	300	
Recharge time:	Less than 3 hours	
Charge temperature:	0°C / +32°F to +45°C /+113°	

Other features

EXPLORER Connect App for IOS and Android*:

The App includes a SIP Softphone converting your Smart Device into a satelilite phone, Terminal Access to control your BGAN and Pointing Assistance.

Will be available for download from Apple App Store and Google Play in November 2014.

EXPLORER LTE Modem for USB*:

With the EXPLORER LTE Modem you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices

* To be confirmed - expected to be available in O1 2015.

Package

- EXPLORER 510 terminal
- Built-in Rechargeable Lithium Ion Battery
- EXPLORER Softbag
- USB to Ethernet Converter Cable
- 100-240VAC Power Supply
- Multi-Languge Quick Start Quide
- Multi-language webserver and embedded manual (ENG, FR, DE, ES, RU, JP and CN)

Accessories

- EXPLORER Softbag (included in the package)
- 100-240VAC power supply
- Car Charger cable
- EXPLORER 4G USB Modem (expected to be available in Q1 2015)

Product number

403711A-00500 **EXPLORER 510 Terminal**

For further information please contact:

Cobham SATCOM Lundtoftegaardsvei 93 D DK-2800 Kgs. Lyngby Denmark

www.cobham.com Tel: +45 3955 8800 Fax: +45 3955 8888